

Clack® 

# WS1TC

## WATER SPECIALIST CONTROL VALVE



- More informative 4 digit LCD Display with Status Indicators
- Solid state microprocessor with easy access front panel settings
- Service flow rate of 27 gpm, backwash 27 gpm
- Backwash and brining ability to 21" diameter tanks
- Front panel display for time of day, days until next regeneration
- Days between regeneration feature: 1-99 days standard; 7-day optional
- Double backwash feature offers optimum regeneration, cleaning ability and efficiency
- 10 selectable pre-programmed regeneration cycles
- Coin Cell Lithium battery back-up with a 8 hour carry over
- Auto detection of 50/60 Hz line frequency, with automatic 12/24 hour time keeping formats
- 12-volt output AC Adapter provides safe and easy installation
- Post treated water regenerant refill
- Patented one piece expanding seal spacer stack assembly U.S. Patent 6,402,944
- Patented linearly reciprocating piston operation U.S. Patent 6,444,127
- Reliable and proven DC drive

# Water Specialist 1" TC Control Specifications

Inlet/Outlet Fittings.....	¾" to 1.5" NPS
Cycles .....	up to 6
Valve Material .....	Noryl (1) or equivalent
Regeneration .....	downflow

## FLOW RATES

Service @15 psi drop (includes bypass) .....	27 gpm
Backwash @ 25 psi drop (includes bypass) .....	27 gpm
Cv Service .....	7.0
Cv Backwash .....	5.4

## OPERATING PRESSURES

Minimum/Maximum .....	20 psi – 125 psi
-----------------------	------------------

## OPERATING TEMPERATURES

Minimum/Maximum .....	40° – 110° F
-----------------------	--------------

## DIMENSIONS & WEIGHT

Distributor Pilot .....	1.050" OD Pipe (¾" NPS)
Drain Line .....	¾" or 1" NPT
Brine Line .....	¾" or ½" OD Poly Tube
Mounting Base.....	2 ½" - 8 NPSM
Height From Top Of Tank.....	7 ¾"
Weight .....	4.5 lbs.

## ELECTRICAL SPECIFICATIONS

	AC Adapter	
	U.S.	International
Supply Voltage .....	120V AC.....	230V AC
Supply Frequency .....	60 Hz .....	50 Hz
Output Voltage .....	12V AC.....	12V AC
Output Current .....	500 mA .....	500 mA

## TANK APPLICATIONS

Water Softener .....	6" – 21" diameter
Water Filter (2).....	6" – 21" diameter

## CYCLES OF OPERATION (Softener Downflow)

Cycle	Range of times minutes
1. Backwash 1 <sup>st</sup> (upflow) .....	3 - 12
2. Regenerate Draw/Slow Rinse (downflow) .....	50 - 70
3. Backwash 2 <sup>nd</sup> (upflow) .....	3 - 12
4. Fast Rinse (downflow) .....	3 - 8
5. Regenerant Refill (in service with treated water).....	As Programmed
6. Service (downflow)	

### Options: Backwash Filter, Bypass, Weather Cover

Compatible with the following typical concentration of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine and chloramines

1. Noryl is a trademark of Sabic Innovative Plastics IP B.V. Company
2. Filter tank size calculated @ 10 gpm of backwash per square foot of bed area