

Produs	Specificatii tehnice Purificatoare apa potabila	
	<p align="center">Filtru Counter-Top</p> <p>Cod FHCTF Dimensiuni [H x D] 330 mm x 115 mm Temperatura de lucru 2°C - 45°C Conexiune alimentare 1/2" Numar O-ring 2 Contine cartus FCCA-STO: elimina sedimente, rugina, clor, anumite pesticide, compusi organici.</p>	
	<p align="center">Filtru Counter-Top-TWIN</p> <p>Cod FHCTF2 Dimensiuni [H x W x L] 260x 130x 330 mm Temperatura de lucru 2°C - 45°C Conexiune alimentare 1/2" Numar O-ring 2 Contine cartuse FCPP10-20, FCCA10: elimina sedimente mai mari de 20 microni, rugina, clor, pesticide</p>	
	<p align="center">Filtru FHPL-TRIPLE</p> <p>Cod FHPL34-D1-TRIPLE Dimensiuni [H x W x L] 390 x 140 x 360 mm Temperatura de lucru 2°C - 45°C Conexiune alimentare 3/4" Presiune 6 bar Numar O-ring 2 Contine cartuse FCPP10-20, FCCA10, FCCB10: elimina sedimente mai mari de 20 microni, rugina, clor</p>	
	<p align="center">Purificator Ultra FT</p> <p>Cod FP3-HJ-K1 Dimensiuni [H x W x L] 395 x 140 x 360 mm Temperatura de lucru 2°C - 45°C Conexiune alimentare 1/2" Presiune de lucru 3.5 bar Set cartuse standard FCPP10-5, FCCST2, FCCBKDF, TLCHF-2T</p>	
	<p align="center">Purificator Aqua-EXCITO</p> <p>Cod EXCITO Dimensiuni [H x W x L] 438x100x360 mm Temperatura de lucru 2°C - 45°C Conexiune alimentare 1/2" Presiune maxima 6 bar Set cartuse standard AIPRO-20MS, AIPRO-1MS, AICRO-L3, AICRO-L4</p>	
	<p align="center">Purificator Aqua-EXCITO-B</p> <p>Cod EXCITO-B Dimensiuni [H x W x L] 438x100x360mm Temperatura de lucru 2°C - 45°C Conexiune alimentare 1/2" Presiune de operare optim 3.5 bar Set cartuse standard si membrana de Ultrafiltrare AIPRO-20M-QM, AISTRO-2-QM, AICRO-3-QM, AICRO-4-QM, TLCHF-2T</p>	